

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Suitable for wall mount applications.
- Universal J-box mounting pattern.
- 120V-277VAC Dual voltage operation.
- 2X 4pcs 2835 LED lamp heads for emergency mode.
- Luminous Flux: more than 200 LM.
- Built-in 3.6V1000mAh Nickel cadmium battery for minimum
- 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40° C indoor damp location listed.

ORDERING INFORMATION

FAMILY	HOUSING COLOR
JLEU12	BLANK(WHITE)
	B(BLACK)

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
JLEU12	40x27x15.5cm/6pcs	4.5/3.5kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
JLEU12	120-277V	0.066A	4.5W	2x4pcs 2835 LED lamp heads	24 Hrs	90 Mins

FAMILY: **JLEU12**

NOTES:

TYPE: **ADJUSTABLE DUAL HEAD EMERGENCY LIGHT**

CEC DOE FC

