

FEATURE

- Injection-molded thermoplastic ABS housing, UL 94V-0 flame rating.
- Innovative, easy installation in minutes.
- Letters 6" height with 3/4" stroke.
- Single or double faces (Universal).
- Universal J-box mounting pattern.
- 120V/277VAC Dual voltage operation.
- Ultra bright RED and GREEN LEDs in one unit, optional by an internal switch after installation.
- Built-in 1.2V1000mAh Ni-MH battery for minimum 90 minutes emergency operation.
- Maximum 24 hours for full recharge time.
- Test switch and charge indicator.
- UL and cULus listed.
- 0° to 40°C indoor damp location listed.

ORDERING INFORMATION

FAMILY	LENS	HOUSING COLOR	OPERATION
EZCXTEU2	R/G	W(WHITE)	BLANK(AC ONLY)
	R/G	B(BLACK)	EM(BATTERY BACKUP)

PACKING INFORMATION

MODEL NO.	PACKING INFORMATION	WEIGHTS
EZCXTEU2BCWEM	38.5X31.5X21.5cm / 6pcs	5.7/4.7kgs

ELECTRICAL INFORMATION

MODEL	RATED VOLTAGE	INPUT CURRENT	INPUT WATT	LED TYPE	CHARGING TIME	EMERGENCY RUN TIME
EZCXTEU2RW	120/277V	0.09A	1.0W	R and G Super bright, long life LED	24 Hrs	90 Mins

FAMILY: **EZCXTEU2B CWEM**

NOTES:

TYPE: **B I- COLOR EMERGENCY EXIT**



CEC DOE FC



*RED&GREEN EXIT 2in1

*Bi-Color Red / Green LED's

